

NO. EM 1(10)95/

10198

22/5/95


*STANDING INSTRUCTION NO. 457

SUB: FIXING OF TILES/BRICK ON EDGE FLOORING
AROUND TRESS ON FOOTPATHS AND ROAD
BERMS.

It has been observed that around the trees, which are planted on roadsides, tiles on footpaths and brick on edge flooring on road berms are provided abutting the tree trunks. Providing tiles/brick on edge flooring in such a manner affects the growth of the tree, In order that growth of the tree is not hampered, all concerned are, therefore, directed to ensure that :

1. Tiles/brick on edge flooring around the trees are provided upto a distance of atleast 1/2 to 2 feet away from the trees.
2. Wherever the tiles/bricks flooring have already been provided abutting the trees, the same should be removed from the area around the tree keeping a distance of atleast 1/2 to 2 feet, so that the existing trees could grow properly.


This issues with the approval of Engineer Member.


(S.M. MADAN)
DIRECTOR(WORKS)

1. ALL CHIEF ENGINEERS
2. DIRECTORS(HORT.)-NORTH & SOUTH
3. DIRECTOR(LANDSCAPE)

Copy to:-

1. OSD to VC, for information with reference to his office D.O.No.PA/VC/95/1056-DA dated 12-5-95.
2. In file No. Em.3(64)88/Hort./Vol.XVII.
3. Guard File.


DIRECTOR(WORKS)